


QFR-K15AD



FIRE RATED STAINLESS STEEL DOOR PUSH RELEASE EXIT BUTTON



115mm x 40mm
1.7mm thickness



NO/NC/COM



Stainless steel



Compact Design



Durable Const.
Corrosion resistance.



Easy Installation



PRODUCT DESCRIPTION

The QFR-K15AD is a fire-rated stainless steel door exit button designed for use in access control systems. This durable button is made from high-quality stainless steel, ensuring long-lasting performance. It supports multiple output contacts, including Normally Open (NO), Normally Closed (NC), and Common (COM), making it versatile for various door exit applications. Additionally, the QFR-K15AD is fire-rated, providing enhanced safety in emergency situations.

PRODUCT ADVANTAGES

Durable Construction: Made from high-grade stainless steel, providing resistance to wear and ensuring longevity.

Fire Rated: Certified for use in fire-rated installations, offering enhanced safety.


Flexible Output Options: Supports NO, NC, and COM output contacts, allowing integration with various access control systems.

Compact Design: The button is designed to fit neatly into standard installations, ensuring a clean and professional look.

Reliable Operation: Built for consistent performance, ensuring reliable door exit functionality in access control setups.

Easy Installation: The simple design allows for quick and secure installation in a variety of environments.

QFR-K15AD



TECHNICAL SPECIFICATION

Product Parameter	Description Parameter
Model	QFR-K15AD
Dimension	115mm x 40mm x 1.7mm thickness
Material	Stainless steel
Current Rating	3A, 36VDC Max
Output Contact	NO/NC/COM
Mechanical Life	1000000 tested
Operating Temperature	-20°C to 55°C (-4°F to 131°F)
Special Feature	Fire Rated
Weight	0.15 Kg
Warranty	3 Years
Country of Origin	Malaysia
Certifications	UL, CE, BS EN 15725: 2010; EN 1634

DIMENSIONS

