

QUANT POWER EDGE ONLINE UPS



QUANT POWER EDGE ONLINE UPS – 10kVA


(3-Phase Tower Type)

High-Density Online Double Conversion UPS

The **QUANT POWER EDGE 10kVA Tower UPS** is an advanced 3-phase online double-conversion uninterruptible power system designed for critical applications requiring superior power protection, high reliability, and intelligent monitoring.

With DSP full-digital control, high-efficiency inverter architecture, and a 7-inch IoT touch LCD, this UPS delivers clean, uninterrupted power to mission-critical IT, medical, industrial, and ELV systems.

Available in internal battery (20/40/80 cells) and external-battery configurations, the POWER EDGE series offers flexible runtime, robust performance, and strong environmental adaptability.



KEY FEATURES

- True Online Double-Conversion
Zero transfer time ensures stable and continuous power.
- 3-Phase Input / 3-Phase Output (3P/3P)
Ideal for enterprise and industrial loads.
- High Power Density
Compact tower design with strong inverter capability.
- 7" Smart Touch LCD with IoT Functions
Real-time monitoring, remote alarms, energy statistics, and event logs.
- Internal or External Battery Options
Space for 20 / 40 / 80 pcs internal 12V batteries
External battery cabinets supported
- Advanced DSP Control
Fast response, stable performance, and high precision.
- Strong Environmental Tolerance
Wide input voltage range, high overload capability, high charging accuracy.
- Comprehensive Protection
Overload, over-voltage, under-voltage, short-circuit, over-temperature, battery protection.
- Standard Breakers Included
Input breaker, Static bypass breaker, Output breaker, Battery Breaker, Maintenance bypass switch

QUANT POWER EDGE ONLINE UPS



TECHNICAL SPECIFICATIONS

MODEL		PE-T010-3I-20B	PE-T010-3X-40B	PE-T010-3X-80B	PE-T010-3X
Rate Power		10kVA			
Main input	Input	3P5W (3P+N+PE)			
	Rate Voltage	380/400/415VAC(L-L) 220/230/240VAC(L-N)			
	Rate Freq.	50/60Hz			
	Input PF	>0.99			
	Current distortion	THDi<2%(100% Linear load)			
	Voltage range				
	Freq. range	40-70Hz			
	Battery	Rate voltage	±120VDC(default 20 PCS,20-50 PCS, selceted)	±240VDC(default 40 PCS,30-50 PCS, selceted)	
Internal BAT		UPS with internal batteries,12VDC/7~9Ah			
Model					
External BAT		UPS for external batteries,Settable			
Quantity		Internal BAT	20PCS	40PCS	80PCS
	External BAT	20PCS(default, 20-50PCS optional)			40PCS(default, 30-50PCS optional)
Charging Internal BAT		4.3%*Pout	8.6%*Pout	17.2%*Pout	8.6%*Pout
capacity		External BAT		50%*Pout	
Charging accuracy		±1%			
Bypass	Rate voltage	380/400/415VAC(L-L)220/230/240VAC(L-N)			
	Voltage range	Range: -40%- +25% , Settable, default -20% +15%			
	Frequency range	50/60Hz Settable ±1Hz ±3Hz ±5Hz			

QUANT POWER EDGE ONLINE UPS



TECHNICAL SPECIFICATIONS

MODEL	PE-T010-3I-20B	PE-T010-3X-40B	PE-T010-3X-80B	PE-T010-3X	
Inverter	Rate voltage	380/400/415VAC(L-L) 220/230/240VAC(L-N)			
	Rate Freq.	50/60Hz			
	Output PF	1			
	Voltage accuracy	±1.0%			
	Output THDu	<1% linear load ,<5% non-linear load according to IEC 62040-3			
	Overload	110%,1 hour 125%,10 mins 150%,1 min >150%,200ms			
	Frequency accuracy	0.001			
	Synchronize window	Settable ±0.5Hz-±5Hz default ±3Hz			
	Slew rate	Settable 0.5Hz/S-3Hz/S default 0.5Hz/S			
	Crest factor	3:01			
Phase Accuracy	120°±0.5°				
System	Efficiency	up to 97%			
	Display	LED + 7 inch touch LCD			
	Certification- Safety	IEC62040-1, IEC60950-1			
	Certification- EMS	IEC62040-2	IEC61000-4-2(ESD)	IEC61000-4-3(RS)	IEC61000-4-4 (EFT) IEC61000-4-5 (Surge)
	Configuration	USB, RS232, RS485, Dry contact, Air filter, Cold start, Ethernet port			
	Option	SNMP card, AS400 card, Parallel kit			
	Environment	0-40 operation -25 ~70 storage 0-95% (Humidity, non-condensing)			

QUANT POWER EDGE ONLINE UPS



TECHNICAL SPECIFICATIONS

MODEL		PE-T010-3I-20B	PE-T010-3X-40B	PE-T010-3X-80B	PE-T010-3X
Dimension (W*D*H) mm	Internal BAT	380/400/415VAC(L-L) 220/230/240VAC(L-N)			
	External BAT	50/60Hz			
Weight(kg)	Internal BAT	1			
	External BAT	±1.0%			
Certifications		CE			
Country of Origin		Malaysia			
Warranty		2 year			

OPTIONS & ACCESSORIES

- SNMP network monitoring card
- AS400 dry-contact card
- External battery cabinets
- Air filter / dust protection
- Cold start and emergency power-off (EPO) features

APPLICATIONS

- Government IT & Data Rooms
- Finance and Banking
- Enterprise IT & Cloud
- Education and Research Centers
- Transportation & Airports
- Medical Diagnostics & Healthcare
- Broadcasting and Telecommunication
- Energy & Industrial Control Rooms

QUANT POWER EDGE ONLINE UPS



ORDERING INFORMATION

Model	Description
PE-T010-3I-20B	10kVA/10kW Tower UPS, PF1.0, Space for 20×12V/9Ah, 7" Touch LCD, excluding batteries
PE-T010-3X	10kVA/10kW Tower UPS, PF1.0, External Battery Type, 7" Touch LCD
PE-T010-3X-40B	10kVA/10kW Tower UPS, PF1.0, Space for 40×12V/9Ah, 7" Touch LCD, excluding batteries
PE-T010-3X-80B	10kVA/10kW Tower UPS, PF1.0, Space for 80×12V/9Ah, 7" Touch LCD, excluding batteries